



COLOR QUICK-DRYING LACQUER

AREA OF APPLICATION

For the protection of different wooden surfaces, as well as veneered and massive furniture indoors, when you want to achieve a visible structure of wood.

PROPERTIES

- colourless top coat
- quick-drying
- good hardness
- does not become yellow
- no unpleasant odours

TECHNICAL DATA	
COMPOSITION	Acrylic binder, water, additives
COLOR SHADES	Colourless
TINTING	/
GLOSS	Glossy, semi-matt
DENSITY	1,0 - 1,1 g/ml
THINNING	Water, up to 10%
EU VOC category and limits	IIA(e), 130 g/l (2010); the product contains: max. 75 g/l
PACKAGING UNITS	0.75 l
SHELF LIFE	The shelf life of an originally sealed and suitably stored product (temperature ranging from +5 °C to +35 °C, in dry place) is indicated on the packaging. MUST NOT FREEZE.

INSTRUCTIONS FOR USE				
APPLICATION METHOD	Thinning	Viscosity (DIN 4 mm)	Nozzle	Pressure
brush (artificial fibers)	as required	/		
spraying	Max. 10%	/	1,2 - 1,5 mm	2 - 3 bar
WORKING CONDITIONS	Paint, air and surface temperature should be at least +15° C, and rel. air humidity under 75%			
DRYING (T = +20° C, rel. humidity 65%)	Dry dust-free in approx. 1 hour, feels dry in 2 - 3 hours, apply the following layer after 4 hours At lower temperatures and higher relative humidity the drying time is extended.			
COVERAGE	Theoretically: 8 - 10 m ² with 1 l and one application The actual consumption depends on wood treatment, the type of wood and the quality of application.			
CLEANING TOOLS	Immediately after use			

SURFACE PREPARATION

1. *Wooden surface*

The humidity must not exceed 15% for coniferous trees, and 12% for deciduous trees. The dry surface is to be sanded and cleaned, and any wax, resin or grease should be removed with **COLOR NITRO THINNER**.

2. *Renovation of old coating*

Undamaged coatings are to be cleaned and sanded, damaged coatings are to be removed completely.

COATING SYSTEMS

SURFACE		SURFACE PREPARATION	PRIMER	TOP COAT
WOOD	indoor	sanding removing impurities	1 - 2x COLOR QUICK-DRYING PRIMING LACQUER	1 - 2x COLOR QUICK-DRYING LACQUER
OLD COATINGS	indoor	cleaning, sanding and removing damaged coatings	/	2x COLOR QUICK-DRYING LACQUER



NOTES AND SPECIAL FEATURES

- In case working temperature is lower than +15 °C, the coating film will not be formed.