



## COLOR INTERIOR WALL PAINT

### AREA OF APPLICATION

For the protection and decoration of interior wall and ceiling surfaces.

It is suitable for the painting of different types of mineral plasters, fibre-cement plates, concrete, plaster-cardboard plates, glass fibres wall paper, wall papers with relief and old coatings.

### CHARACTERISTICS

- Health and environment friendly paint,
- Suitable for frequent renovation of wall surfaces
- Easy application
- High vapour permeability
- Resistant to dry wiping

TECHNICAL DATA	
PRODUCT TYPE	Copolymer dispersion, pigment, fillers and additives
COLOUR SHADES	White, HGMIX
GLOSS (EN 13 300)	Matt
DENSITY	1,64- 1,68 g/ml
WET SCRUBB RESISTANCE (EN 13 300)	Cl. 5
THINNING	Water, 10-15%
EU VOC category and limits	IIA (a), 30 g/l (2010); product contains: max. 8 g/l
PACKAGING	5 l, 14 l, 40 kg
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5°C to +35°C, in dry place) is until the date indicated on packaging. <b>Prevent freezing.</b>

INSTRUCTIONS FOR USE	
APPLICATION	Roller, brush
WORKING CONDITIONS	Min. +5 °C air, surface and paint
DRYING (T = +20 °C, rel.hum. 65%)	The coating is dry and suitable for overcoating after 4 – 6 hours
COVERAGE	Theoretically: 4 – 6 m <sup>2</sup> with 1 l in 2 coats Practical consumption depending on permeability and surface roughness.
ČIŠČENJE ORODJA	Immediately after use with water

### COATING SYSTEMS

SURFACE	SURFACE PREPARATION	IMPREGNATION	TOP COAT
New, non-painted surface		1x <b>COLOR penetration 1:5</b>	2 –3x <b>COLOR interior wall paint</b>
Painted with emulsion paints - several layers of permeable, non-washable coatings - smooth, glossy, washable coatings	cleaning, removal of crumbly particles, repair of damaged spots cleaning, sanding	1x <b>COLOR penetration 1:5</b>	

### REMARKS AND SPECIALTIES

- Mix paint thoroughly before use.
- Drying time increases at low temperatures and higher air humidity..
- If you thin paint with a larger quantity of water than prescribed, hiding power of paint film will be reduced accordingly.
- **HGMIX** – due to deviation in raw materials between individual batches, minor differences in a colour shade are possible – for larger quantities of the same shade we recommend to use the same batch.
- Paint can be tinted with ready-made pigment concentrate up to max. 3%. Prepare enough of the tinted paint for the whole surface to be painted

I-2020

