



COLOR INTERIOR WALL PAINT

AREA OF APPLICATION

For the protection and decoration of interior wall and ceiling surfaces.

It is suitable for the painting of different types of mineral plasters, fibre-cement plates, concrete, plaster-cardboard plates, glass fibres wall paper, wall papers with relief and old coatings.

CHARACTERISTICS

- Suitable for frequent renovation of wall surfaces
- Easy application
- High vapour permeability
- Resistant to dry wiping

TECHNICAL DATA	
PRODUCT TYPE	Copolymer dispersion, pigment, fillers and additives
COLOUR SHADES	White, HGMIX
GLOSS (EN 13 300)	Matt
DENSITY	1,64- 1,68 g/ml
WET SCRUBB RESISTANCE (EN 13 300)	Cl. 5
THINNING	Water, 10-15%
EU VOC category and limits	IIA (a), 30 g/l (2010); product contains: max. 8 g/l
PACKAGING	5 l, 10 l, 14 l, 40 kg
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5°C to +35°C, in dry place) is until the date indicated on packaging. Prevent freezing.

INSTRUCTIONS FOR USE	
APPLICATION	Roller, brush
WORKING CONDITIONS	Min. +5 °C air, surface and paint
DRYING (T = +20 °C, rel.hum. 65%)	The coating is dry and suitable for overcoating after 4 – 6 hours
COVERAGE	Theoretically: 4 – 6 m ² with 1 l in 2 coats Practical consumption depending on permeability and surface roughness.
ČIŠČENJE ORODJA	Immediately after use with water

COATING SYSTEMS

SURFACE	SURFACE PREPARATION	IMPREGNATION	TOP COAT
New, non-painted surface		1x COLOR penetration 1:5	2 –3x COLOR interior wall paint
Painted with emulsion paints - several layers of permeable, non-washable coatings - smooth, glossy, washable coatings	cleaning, removal of crumbly particles, repair of damaged spots cleaning, sanding	1x COLOR penetration 1:5	

REMARKS AND SPECIALTIES

- Mix paint thoroughly before use.
- Drying time increases at low temperatures and higher air humidity..
- If you thin paint with a larger quantity of water than prescribed, hiding power of paint film will be reduced accordingly.
- **HGMIX** – due to deviation in raw materials between individual batches, minor differences in a colour shade are possible – for larger quantities of the same shade we recommend to use the same batch.
- Paint can be tinted with ready-made pigment concentrate up to max. 3%. Prepare enough of the tinted paint for the whole surface to be painted